

<b>TECHNICAL DATA SHEET</b>	<b>CHEMLINE INDIA LIMITED</b>
Rev 1.2 18/01/2005 <b>CHEMIGUM AC-45 F</b>	F-1 , Sarda Chamber-1 , Central Market Prashant Vihar (Rohini) , Delhi –110085 Tel No : 27555999 , Fax No : 27555991/92

### AREA OF APPLICATION

**CHEMIGUM AC-45 F** is suitable for packaging operations on automatic / semi automatic high-speed machines for paper-to-paper, duplex board corrugation etc. bonding. Can be used as it is or after dilution

### SPECIFIC ADVANTAGES

- **Good Machinability and works well under varying climatic conditions.**
- **No tendency to impart off flavor when used for food Packaging.**
- **Superior bond formation between Aluminium Foil and Paper**

### SPECIFICATIONS

Appearance	Milky White emulsion
Viscosity	28000 ± 2000 cps (Spindle No. 6, RPM – 10, Temperature – 25°)
Film	Forms a translucent, continuous film on paper
pH	5.0 to 6.0
Solid	34 ± 1.0

### HEALTH AND SAFETY

- CHEMIGUM AC-45 F** is non-toxic, non-hazardous and non-flammable under normal conditions of use.
- Splashes in the eyes should be immediately washed with plenty of water.
- Spillage in work place and on cloth should be immediately washed with water.
- Proper ventilation should be provided in work area.

**STORAGE:** Store in air tight containers as supplied, storage should be between 10-35° C. Shelf life is approximately 6–12 months from the date of manufacture. Product should be stirred well before use. Rotate stocks on first in first out basis.

**NB:** - The above data/information and suggestion contained in this literature are based on our study and experience. We recommend that before using our products in full scale production, the customer should make his own tests to determine the suitability of the products. Our field staff and technical personnel shall be happy to assist you in your tests.